



# IC - SOCKET 8604

FCI

Table-1

Transverse pitch	Number of contacts DIL support		Dimension in mm		
			A	B	C
3/10"(7.62 mm)	Code 3	6	7.60	10.10	7.62
		8	10.10	10.10	7.62
		10	12.60	10.10	7.62
		14	17.70	10.10	7.62
		16	20.30	10.10	7.62
		18	22.80	10.10	7.62
		20	25.30	10.10	7.62
		22	27.80	10.10	7.62
		24	30.40	10.10	7.62
		28	35.50	10.10	7.62
4/10" (10.16mm)	Code 4	22	27.80	12.60	10.16
		24	30.40	12.60	10.16
		32	40.60	12.60	10.16
6/10"(15.24mm)	Code 6	24	30.40	1.70	15.24
		28	35.50	17.70	15.24
		32	40.60	17.70	15.24
		40	50.60	17.70	15.24
		48	60.80	17.70	15.24
9/10" (22.86 mm)	Code 9	64	81.10	25.30	22.86
SIL (Strip)	Code 1	64	162.40	-	-



Ordering Information

Basic Series 8604                      6                      24                      14                      1                      0

**Transverse pitch**

Dil	7.62 (3/10")	3	
	10.16 (4/10")	4	
	15.24(6/10")	6	
	22.86(9/10")	9	
Sil	Stri	1	

Number of contacts: See Table 1

**Terminations**

Straight Spill                      14  
 Wire wrap                      15

**Contact (Clip) finish**

Economic Class                      0 tin over nickel  
 Industrial Class                      1(Low gold over nickel)  
 Professional Class                      2(Medium gold over nickel)  
 High-Performance class                      3(High gold over nickel)

Pin (Sleeve) finish    :    0 tin