



Type No.	No. Of Contacts	Dimensions						
		A	B	C	D	E	F	G
EC-12/P/S	12	69.4	55.6	55.7	51.8	7.0	12.2	5.5
EC-22/P/S	22	109.2	102.5	95.3	91.5	7.0	12.2	5.5

Solder Eyelets. Gold / Silver or Tin Plated (Phenolic or DAP Insulator)

Specifications

Type:	Single Sided Edge Connector,
Temperature(Max):	80 Deg. C
V / A Rating:	5 Amp. 250Vac
Mounting:	Screw-type
Material Contacts:	PB - Gold, Silver or Tin Plated
Material Body:	Phenolic or DAP Insulator
Insulation Resistance(Min):	1000 M Ohms
H. V. Break Down:	1.5 KV
Contact Resistance, Max(Initial):	10 m Ohms
Card Thickness:	1.42 mm - 1.8 mm
No. of Contacts:	12,16,22
Terminals:	Solder-type



Indian Technological Products Private Limited

22-23, Type-B, Hartron Complex, Electronic City, Sector-18, Udyog Vihar, Gurgaon -122 016, Haryana (India)

Telephone: +91-124-4013646, 4013647 • Fax: +91-124-2398277

Email: sales@itpindia.in • www.itpindia.com • CIN: U74899DL1986PTC023265