



**RFI/EMI filter, 6 A, Chassis type**

**Specifications**

Mounting :	Chasis-type
High Voltage test for 60 sec.:	2 KVAC between P & N shorted together & Earth
Voltage Drop:	1 Volt . max.
Insulation Resistance at 500 VDC:	300 M ohms min. between P & N shorted together & Earth
Rated Voltage:	250V AC, 50Hz, 1 Phase .
Rated Current:	6 Amp.
Output Connection:	Fast On 6.3 X 0.8 mm / Solder-type
Operating Temperature Range:	0 to 85 Deg. C.
Input Connection:	Fast On 6.3 X 0.8 mm / Solder-type
Leakage Current:	2 x 0.3 mA
Application:	Power Supplies, Photocopiers, General Instrumentation.

**Use Suffix `SS' to specify Filter with Surge Suppressor e.g. EP-6AP-SS**



**Indian Technological Products Private Limited**

22-23, Type-B, Hartron Complex, Electronic City, Sector-18, Udyog Vihar, Gurgaon -122 016, Haryana (India)

Telephone: +91-124-4013646, 4013647 • Fax: +91-124-2398277

Email: sales@itpindia.in • [www.itpindia.com](http://www.itpindia.com) • CIN: U74899DL1986PTC023265