






LJQX-38F Series

LJQX-38F 系列 Series




產品型號 Model	LJQX-38F		LJQX-38F/T
外形尺寸(毫米) Dimension(mm)	55.4×41.5×49.1		67.6×37.4×57.3
觸點形式 Contact Form	3Z 3H 3D		3Z 3H 3D
觸點材料 Contact Material	銀合金 Silver alloy		
觸點容量阻性 Resistance Performance Of Contactor Capacity	30A/40A/28VDC 30A/40A/250VAC		
線圈功率Coil Power at 23℃	DC(W)	< 1.5W	
	AC(VA)	< 2.5VA	
線圈電壓Coil Voltage	DC(V)	6~220V	
	AC(V)	6~380V	
吸合電壓 Pick-up Voltage at 23℃	DC ≤ 75% AC ≤ 80%		
釋放電壓 Drop-out Voltage at 23℃	DC ≥ 10% AC ≥ 30%		
最大電壓 Max Voltage at 23℃	110%		
接觸電阻 Contact Resistance(at 6VDC 1A)	≤ 100mΩ		
介質耐壓 Dielectric Strength	開路觸點間 Between Open Contacts	≥ 1200VAC 50Hz/1min 漏電流 Leakage current 1mA	
	觸點組間 Contacts pieces	≥ 1500VAC 50Hz/1min 漏電流 Leakage current 1mA	
	線圈觸點間 Between Coil & Contacts	≥ 1500VAC 50Hz/1min 漏電流 Leakage current 1mA	
絕緣電阻 Insulation Resistance(MΩ)at 500VDC	≥ 1000MΩ		
工作壽命 Service life	電氣(次) Electrical	10 ⁷ Times(頻率Frequency: 通On1次Time/1S, 斷Off1次Time/1S)	
	機械(次) Mechanical	10 ⁷ Times(頻率Frequency: 300次Time/1min)	
環境溫度 Ambient Temperature	-25℃~+55℃		
引出端形式 Terminal type	插入式Insert type		
配用插座 Suitable socket	38F11A		
產品重量(g) Product Weight	130g		135g
同類型參照 Same Reference			

LJQX-38F 安裝尺寸和接線圖 Installation dimensions and connecting diagram



LJQX-38F 接引線式 Connecting lead wire type



LJQX-38FT 安裝尺寸和接線圖 Installation dimensions and connecting diagram

