



MS-1 with rivetted body

Specifications

Reference Standard:	IEC 61058
Mechanical Life:	50,000 Cycles min .
Permissible Temp For With/Without Load:	-20 deg. C. to +85 deg. C
Permissible Temp For Soldering:	270 deg. C. / 5sec. max .
Operating Force:	200 gms. +/-50gms .
Material - Terminals:	Copper alloy, Tin / Silver plated
Terminals:	Solder - type
Insulation Resistance(Min):	100 M Ohms at 500 VDC
H. V. Breakdown Test:	1 KVAC For 1 Minute .
Electrical Life:	10000 Cycles Min.
Materials - Body:	PBT
Contact Resistance(Max, Initial):	20 m Ohms
Colours Available For Actuator:	NA
Contact & Voltage Rating:	4 A, 250V AC
Switch Type:	Momentary SPDT Micro Switch
Contact Arrangement:	NO / NC



Indian Technological Products Private Limited

22-23, Type-B, Hartron Complex, Electronic City, Sector-18, Udyog Vihar, Gurgaon -122 016, Haryana (India)
 Telephone: +91-124-4013646, 4013647 • Fax: +91-124-2398277
 Email: sales@itpindia.in • www.itpindia.com • CIN: U74899DL1986PTC023265