



## Specifications

Switch Type:	Momentary - Square Head
Permissible Temp For Soldering:	270 deg. C for 5 sec. max.
Permissible Temp For With/Without Load:	-20 deg. C to +85 deg. C
Terminal Style:	Solder-type
Colours Available For Housing:	Bk .
Colours Available For Rocker:	Rd / Bk / Gn / Yl / Bl / Wh
Product Weight:	4.7 gm .
Mounting:	Panel, Screw-type
Mechanical Life:	50,000 Cycles
Material - Terminals:	Copper, Silver plated
Contact Arrangement:	SPST
Contact & Voltage Ratings:	3 A, 250V AC
Contact Resistance(Max Initial):	10 m Ohms
Electrical Life:	10,000 Cycles
H. V. Breakdown Test:	1.5 KVAC For 1 minute
Insulation Resistance at 500V DC (Min):	100 M Ohms
Material - Body:	Nylon



### Indian Technological Products Private Limited

22-23, Type-B, Hartron Complex, Electronic City, Sector-18, Udyog Vihar, Gurgaon -122 016, Haryana (India)

Telephone: +91-124-4013646, 4013647 • Fax: +91-124-2398277

Email: sales@itpindia.in • [www.itpindia.com](http://www.itpindia.com) • CIN: U74899DL1986PTC023265