



	A	B	C	D	E	F	G	H	I	J	K	L
PCS - 14	$(7.62 \times n) + 5$	$(7.62 \times n) + 3$	$(7.62 \times n) + 3.3$	15	2.5	7.62	3.8	14	10	6	34	14.5

Specifications

Permissible Temp. for Soldering:	270 deg. C for 5 sec.
Operating Temperature:	-20 deg. C to +85 deg. C
Continuous Current:	1 Amp. MAX.
Life:	10,000 Cycles (With load)
Insulation Resistance(Min):	100 M Ohm at 500 VDC
Dielectric Strength:	500 VAC for 1 minute
Contact Resistance, Max(Initial):	200 m ohm
V/A Rating:	100 mA, 50 VAC / 28 VDC
Height:	14 mm
Type:	Switch with Binary Output
Material - Housing:	Engineering Thermoplastics
Mounting:	Panel, Snap-in type
Panel Thickness:	0.80 - 2.00



Indian Technological Products Private Limited

22-23, Type-B, Hartron Complex, Electronic City, Sector-18, Udyog Vihar, Gurgaon -122 016, Haryana (India)

Telephone: +91-124-4013646, 4013647 • Fax: +91-124-2398277

Email: sales@itpindia.in • www.itpindia.com • CIN: U74899DL1986PTC023265