


C-DOT, CE
Specifications

Contact Arrangement:	DPST
Mounting:	Panel, Snap-in type
Permissible Temp with / without Load:	-20 deg. C to + 85 deg. C
Permissible Temp For Soldering:	270 deg. C for 5 sec. max.
Test Specifications:	IEC - 1058 - 1(1996)
Terminal Style:	Solder-type / Fast-on 4.8 x 0.8
Product Weight:	4.3 gm.
Material For Housing:	Nylon
Insulation Resistance (Min.):	100 M Ohms at 500 VDC
H. V. Breakdown Test:	1.5 KVAC For 1 Minute
Electrical Life:	10000 Cycles .
Material - Terminals:	Terminals-Brass, Silver plated
Contact Resistance(Max, Initial):	10 m Ohms
Colours Available For Rocker:	Rd / Gn / Bk
Colours Available For Housing:	Bk
V/A Rating:	4 A, 250V AC
Type:	Non-Illuminated
Panel Thickness:	3.00 max.


Indian Technological Products Private Limited

22-23, Type-B, Hartron Complex, Electronic City, Sector-18, Udyog Vihar, Gurgaon -122 016, Haryana (India)

Telephone: +91-124-4013646, 4013647 • Fax: +91-124-2398277

 Email: sales@itpindia.in • www.itpindia.com • CIN: U74899DL1986PTC023265