



Specifications

| | |
|---------------------------------------|---|
| Contact Arrangement: | SPST |
| Mounting: | Panel, Snap-in type / PCB mounting |
| Permissible Temp with / without Load: | -20 deg. C to + 85 deg. C |
| Permissible Temp For Soldering: | 270 deg. C for 5 sec. max. |
| Test Specifications: | 1EC - 1058 - 1 : 1996 . |
| Terminal Style: | Solder-type |
| Material For Housing: | Nylon |
| Insulation Resistance (Min.): | 100 M Ohms at 500 VDC |
| H. V. Breakdown Test: | 1.5 KVAC For 1 Minute |
| Electrical Life: | 10,000 Cycles |
| Material - Terminals: | Terminals-Brass / Copper, Silver plated |
| Contact Resistance(Max, Initial): | 10 m Ohms |
| Colours Available For Rocker: | Rd / Bk / Gn / Wh |
| Colours Available For Housing: | Bk |
| V/A Rating: | 4 A, 250V AC |
| Type: | Switch with PCB mountable terminals |
| Panel Thickness: | 3.00 max. |



Indian Technological Products Private Limited

22-23, Type-B, Hartron Complex, Electronic City, Sector-18, Udyog Vihar, Gurgaon -122 016, Haryana (India)

Telephone: +91-124-4013646, 4013647 • Fax: +91-124-2398277

Email: sales@itpindia.in • www.itpindia.com • CIN: U74899DL1986PTC023265